

Hadrian Tridi-Systems P.O. Box 1747 Vista, California 92085

Dec. 8, 2003

Attn: Loran

Regarding: Strength of Tridipanel Wall System

The panel receives its strength from the many nine gauge wires, which are welded from the face of the wire on one side thru the foam and then welded to the wire on the opposite side of the panel. This happens every 4 inches or 10mm. This actually Is like placing 12 steel studs into each panel with the panel still having the foam core for insulation, for additional strength you may add re-bars before placing the shotcrete, this wall system is very strong, the testing shown on the wall panel with cement will hold up to over 200,000 pounds. I don't know the metric equivalent, this is why it does not damage easily, I hope this answers your question!

Sincerely,

Rod Hadrian

Hadrian Tridi Systems

TEST DATA

TEST #6

WALLS TESTED: #15, #16, #17

SPECIMEN PARAMETERS


Average Wall Height	Reinforcing Steel Gauge	Total Concrete Thickness	Insulation Thickness	Average Concrete Strength	
20'	11	3"	2-1/2	e	

TEST PARAMETERS

Wall I.D.	Load at Failure	Failure Type			
15 16 17	141,000 lbs 174,000 105,000	Wall Top, Compression shear			

Average compression # 100 kip load: 0.021 inches

Average bending deflection @ 100 kip load: 0.13 inches



4

 ${\bf e}_{i,j}$

١.

TEST DATA

TEST #7

WALLS TESTED: #18, #19, #20

SPECIMEN PARAMETERS

)

Average Wall Height				Total Concrete <u>Thickness</u>		Average Concrete Strength	
20'	i i	11	3"		3-1/2"		

TEST PARAMETERS

Wall I.D.		Load <u>at Failure</u>			Failure Type				
	18 19 20	*	201,000	lbs .		Wall	Top,	Compression	shear
21	20		120,000		8 ,			at .	-

Average compression @ 100 kip load: 0.016 inches

Average bending deflection @ 100 kip load: 0.10 inches

ASTM E72 COMPRESSION TEST 20' WALL, 11 GAUGE, 3.0 INCHES CONCRETE

